

Product information Sheet TUSK Wall Mounted Racks Specification

32

Locations for use: Residential, Workplace, Garages, Basement bike storage, in fact anywhere there is a wall.

Items required: 200mm Rack (Wall face to centre of hook). In **Red** or **Black**



TUSK Rack (200mm) Red [R200R]

- One piece MIG welded steel assembly
- 5 year warranty
- Stoved powder coat signal red
- Security loop provision for D-lock
- 2 x M6 expanding wallbolts included
- Sheathed Hooks for frame /wheel protection
- Overall Dims. 200mm from wall face to centre of hook. Fixing centres at 60mm crs.



TUSK Rack (200mm) Black [R200B]

- One piece MIG welded steel assembly
- 5 year warranty
- Black corrosion proof finish Plascoat PPA 571
- Security loop provision for D-lock
- 6 x M6 expanding wallbolts provide
- Sheathed Hooks for frame / wheel protection
- Overall Dims. 200mm from wall face to centre of hook. Fixing centres at 60mm crs.

General: Horizontal racking for any standard drop handlebar road bike. Held by top tube. Vertical racking for any bike by hanging with handlebars and saddle to the wall with a hook either side of handlebar stem. **One** rack per bike. Use a bike D-lock or chain / cable passing through the security side loop to secure the bike to the rack. Consider also fitting an Excel Security Anchor for Maximum security. For horizontally racking wide handlebar bikes against the wall horizontally use the **BullRack** Bike cradle available on this site.

See website for full Terms and Conditions and further details.

www.tuskstore.com