

Product information Sheet TUSK Hook'n'Hang Bike Rack Specification

30

Locations for use: Residential, Workplace and employee bike parking, Garages, Community and Public areas, basement bike storage, single units or by the hundreds.
Items required: HNH/Rack; HNH/Lower Guide, 14mm Masonry Drill.



HNH Bike Rack Specification:

- One piece MIG welded steel assembly
- Virtually indestructible, 5 year warranty
- Black corrosion proof finish Plascoat PPA 571
- Dual Security loops provision for locking
- 2 x M8 Heavy duty wallbolts @106mm centres
- Sheathed Hook for wheel protection
- Overall Dimensions: 150mm long x 80mm wide x 130mm max. height.

HNH Lower Guide Specification:

- One piece MIG welded steel assembly
- Virtually indestructible, 5 year warranty
- Black corrosion proof finish Plascoat PPA571
- Dual security loops provision for locking
- 2 x M8 Heavy duty wallbolts @ 190mm centres
- Dimensions: 225mm long x 190mm wide
- Provides an extra optional for additional security and stability in crowded cycle sheds

General: Racks any bike vertically held by the front wheel, 20mm to 65mm wide. No accidental dislodging. No buckled wheels. No needless pavement clutter when not in use; maximum protrusion is only 130mm. See additional data sheets for compact, high density installations. You will also require a 14mm Masonry drill. **Architect approved for, and installed in 2012 Olympic Athletes Village.**

See website for full Terms and Conditions and further details.

www.tuskstore.com

