



Detail Sheet **13A**

SHIELD ANCHOR INSTALLATION

Bull Rack, Hook n Hang, Excel Security Anchors

SHELFORD DESIGN LTD

Unit 10 Blagdons Storage
250 Embankment Road
Plymouth
Devon
PL4 9JH



Installation:

1. Locate at suitable height in sound masonry; mark hole centres, drill a 14mm x 55mm deep hole at each location and clean out holes.
2. Finger tighten bolts into shield anchors prior to inserting into the wall.
3. Tap flush with wall face, give 2-3 turns of bolts to expand the anchor.
4. Remove bolts.
5. Attach Bull Rack as shown with 2 x M8 x 60mm bolts with a washer under each bolt head and fully tighten. Recommended torque is 25Nm.
6. Check Bull Rack is level using a spirit level. Add plastic bolt head covers.
7. Rack bike horizontally as shown by top tube, or vertically by seat tube.
8. Lock bike to Bull Rack using a quality security cable through both locking loops, through

These instructions are for information only. Should you have any questions, please contact us and we will do our best to help you.

Telephone support: +44 (0) 7767 484465

Email support: sales@tuskstore.com

TUSK is a registered Trade Mark of Shelford Design Ltd. Company Reg No: 1905093 VAT Registered Number: 393261640
S QUICK: Managing Director

Telephone support: +44 (0) 7767 484465
Email support: sales@tuskstore.com